(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 8 January 2004 (08.01.2004)

PCT

English

US

(10) International Publication Number WO 2004/002648 A2

(51) International Patent Classification7: B21D 39/00

(21) International Application Number: PCT/US2003/019122

17 June 2003 (17.06.2003) (22) International Filing Date:

(25) Filing Language:

(26) Publication Language: English

(30) Priority Data: 26 June 2002 (26.06.2002) 60/392,016

(71) Applicant (for all designated States except US): TESCO ENGINEERING, INC. [US/US]; 1900 Brown Road, Auburn Hills, MI 48326 (US).

(72) Inventors: and

(75) Inventors/Applicants (for US only): STEED, James, J., Jr. [US/US]; 648 North Perry, Pontiac, MI 48342 (US). TOENISKOETTER, James, B. [US/US]; 3666 Hollenshade, Rochester Hills, MI 48306 (US).

(74) Agent: FILDES, Christopher, J.; Fildes & Outland, P.C., 20916 Mack Avenue, Suite 2, Grosse Pointe Woods, MI 48236 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PORTABLE HEMMING APPARATUS AND METHOD

(57) Abstract: A portable hemming apparatus includes a support structure, a plurality of modular self-contained hemmers disposed about the support structure and at least one pneumatic drive mounted on the support structure. Each modular hemmer includes a hem die holder, a hem die fixed to the hem die holder and a movable hem punch. A hem operator is operatively connected to each modular hemmer. Each hem operator is a lever arm assembly. Actuation of the drive moves the hem operators and causes the hem punches to close and open on the hem die, allowing for the hemming of a metal panel located within the modular hemmers. The support structure of the hemming apparatus can be adapted to be mounted on a robot arm, mounted on a pedestal stand, or hung from a tool balancer. These arrangements allow for various uses of the hemming apparatus. Further, the modular design of the hemmers allows the apparatus to be used for the hemming of various sizes and shapes of panels.

